

DECLARATION OF PERFORMANCE

Date of issue: 4/19/2016
Replaces: No --- - CPR --/--- - yyyy/# of: dd/mm/yyyy

No. 0761-CPR-15/0243-2016/04

1 **Unique identification of the product-type:** **PROMASTOP®-B**

2 **Type and batch numbers:** as given on the packaging of the product

3 **Intended uses** as given in the ETA-15/0243:
 3.1 - PROMASTOP®-B is a prefabricated, permanent elastic fire stopping brick for combustible and non-combustible pipes (with combustible insulation), cables and cable bundles in penetrations in walls and floors.
 3.2 - The product is intended for:
 - use at internal conditions with humidity < 85% RH, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z2)
 - use at internal conditions with humidity ≥ 85%, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z1);
 - use at temperatures below 0°C, but no exposure to rain or UV (TR 024:2009, type Y2);
 - use at temperatures below 0°C, with exposure to UV but no exposure to rain (TR 024:2009, type Y1);

4 **Name and contact address of the manufacturer:**
 Promat International NV
 Bormstraat 24
 B-2380 Tiselt
 Belgium
 Plant :13
 www.promat-international.com

5 **Authorised representative:** not applicable.

6 **System or systems of Assessment and Verification of Constancy of Performance (AVCP):** see table under section 9.

7 **The construction product is not covered by a harmonised standard (hEN).**

8 **The declaration of performance concerns a construction product for which a European Technical Assessment has been issued.**
 The Österreichische Institut für Bautechnik (OIB, Austria) has issued an ETA for this product with no. ETA-15/0243 based on ETAG 026-1 and ETAG 026-2..
 Notified product certification body: No. 0761 (MPA Braunschweig)
 Certificate of Constancy of Performance
 0761 - CPR - 0512

9 Declared performance			
Essential characteristics	AVCP systems	Performance	Harmonised technical specification
BR1: Mechanical resistance and stability.			
BR2: Safety in the case of fire:			
Reaction to fire:	1	E.	ETA 15/0243
Resistance to fire:	1	This characteristic depends on the tested assembly. A fire resistant construction, in which the product was used, has been tested and the performance class has been established in a classification document in accordance with the applicable part of EN 13501.	
BR3: Hygiene, Health and the Environment:			
Air permeability:	-	NPD (No Performance Declared)	ETA 15/0243
Water impermeability:	-	NPD (No Performance Declared)	
Release of dangerous substances:	-	Declaration (filed with the Technical Approval Body)	
BR4: Safety and accessibility in use:			
Mechanical resistance and stability:		NPD (No Performance Declared)	ETA 15/0243
Resistance to impact and movement:	-	NPD (No Performance Declared)	

Adhesion:		NPD (No Performance Declared)	
BR5: Protection against noise:			
Airborne sound insulation:		NPD (No Performance Declared)	ETA 15/0243
BR6: Energy Economy and Heat Retention:			
Thermal conductivity:	-	NPD (No Performance Declared)	ETA 15/0243
Water vapour permeability (transmission coefficient):	-	NPD (No Performance Declared)	
Durability:			
Basic durability assessment:		In accordance with the declared use, class Z2, Z1, Y2, Y1 according EOTA TR024 and in conformity with ETAG 026-2.	ETA 15/0243

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

The reader of this document is invited to verify on the website www.promat-ce.eu the relevant version.

The product information sheet on the basis of Safety Data Sheet according VO (EG) 1907/2006 for PROMASTOP®-B is available on request.

Signed for and on behalf of the manufacturer by:

Name: Bettina Rothböck
 Function: Product Manager Fire Stopping & Intumescent Seals

Linz, 4/19/2016

Signature: